NSN 5925-01-309-1553



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-309-1553 **Body Style:** Rectangular dimensional envelope **Overall Length:** 3.500 inches **Overall Height:** 2.310 inches **Overall Width:** 2.910 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 3 clip Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 80.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 1 toggle **Actuator Function:**

Actuator Position Designation: At pole two

Trip-reset

NSN 5925-01-309-1553

Circuit Breaker - Page 2 of 2



| Inclosure Protection Type For Which Designed: |
|---|
| General purpose |
| Trip Release Ambient Tempurature Rating: |
| 40.0 degrees celsius all locations |
| Frequency In Hertz: |
| 60.0 all locations |
| Terminal Type And Quantity: |
| 6 compression |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No Fiig: A030a0