

View Online at <https://aerobasegroup.com/nsn/5925-01-309-7356>

Body Length:

2.265 inches

Body Width:

2.000 inches

Center To Center Distance Between Terminals Parallel To Length:

0.750 inches

Center To Center Distance Between Terminals Parallel To Width:

1.530 inches

Mounting Surface To Terminal End Distance:

2.102 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

3 threaded hole

Features Provided:

High inrush protection

Maximum Continuous Load Current Rating Per Pole:

1.75 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations and instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Reset

Auxiliary Switch Function And Quantity:

3 control

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 150 pct all locations and 60.000 at 150 pct all locations

Switch Terminal Type:

Tab, solder lug

Special Features:

With auxilliary contacts

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0