

View Online at <https://aerobasegroup.com/nsn/5925-01-309-7356>

**Body Length:**

2.265 inches

**Body Width:**

2.000 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.750 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.530 inches

**Mounting Surface To Terminal End Distance:**

2.102 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

3 threaded hole

**Features Provided:**

High inrush protection

**Maximum Continuous Load Current Rating Per Pole:**

1.75 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations and instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

150.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Reset

**Auxiliary Switch Function And Quantity:**

3 control

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

6.000 at 150 pct all locations and 60.000 at 150 pct all locations

**Switch Terminal Type:**

Tab, solder lug

**Special Features:**

With auxilliary contacts

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0