

View Online at <https://aerobasegroup.com/nsn/5925-01-309-9218>

Body Style:

Rectangular dimensional envelope

Overall Length:

1.823 inches

Overall Height:

0.400 inches

Overall Width:

1.560 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 clip

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

7.0 amperes ac first location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

0.300 at 135 pct all locations and 7.000 at 135 pct all locations

Inclosure Protection Type For Which Designed:

Dustproof and general purpose

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0