

View Online at <https://aerobasegroup.com/nsn/5925-01-310-1312>

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.332 inches and 0.380 inches

Center To Center Distance Between Terminals Parallel To Length:

0.625 inches

End Application:

T-1348/spg cg48, transmit, radar

Mounting Surface To Terminal End Distance:

1.828 inches

Pole Quantity:

2

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations and 5.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 50.0 dc all locations

Circuit Protection Type:

Overvoltage all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Trip Delay Time In Seconds Per Rated Continuous Current:

0.200 at 135 pct all locations and 7.000 at 135 pct all locations

Frequency In Hertz:

60.0 all locations or 400.0 all locations

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0

Mil-std (military Standard):

Mil-prf-39019 spec.