

View Online at <https://aerobasegroup.com/nsn/5925-01-310-1312>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

Between 0.332 inches and 0.380 inches

**Center To Center Distance Between Terminals Parallel To Length:**

0.625 inches

**End Application:**

T-1348/spg cg48, transmit, radar

**Mounting Surface To Terminal End Distance:**

1.828 inches

**Pole Quantity:**

2

**Maximum Continuous Load Current Rating Per Pole:**

5.0 amperes ac all locations and 5.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations and 50.0 dc all locations

**Circuit Protection Type:**

Overvoltage all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.200 at 135 pct all locations and 7.000 at 135 pct all locations

**Frequency In Hertz:**

60.0 all locations or 400.0 all locations

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0

**Mil-std (military Standard):**

Mil-prf-39019 spec.