

View Online at <https://aerobasegroup.com/nsn/5925-01-310-1887>

**Body Style:**

Single pole type

**Case Material:**

Plastic

**Fragility Factor:**

Moderately rugged

**End Application:**

Mrap buffalo mk2a2

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 clip

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

10.0 amperes ac single location and 10.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac single location and 65.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

200.0 ac single location and 200.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal-magnetic single location

**Trip Release Characteristic:**

Instantaneous single location and time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

140.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Reset

**Actuator Position Designation:**

At pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

10.000 at 200 pct single location and 40.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Shock resistant and vibration resistant

**Trip Release Ambient Temperature Rating:**

21.1 degrees celsius single location

**Frequency In Hertz:**

50.0 single location or 60.0 single location

**Terminal Type And Quantity:**

2 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0