

View Online at <https://aerobasegroup.com/nsn/5925-01-310-1888>

Body Style:

Single pole type

Body Length:

Between 2.050 inches and 2.070 inches

Body Width:

Between 0.970 inches and 0.990 inches

Body Height:

Between 1.620 inches and 1.640 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.310 inches and 0.330 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 clip

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

3.0 amperes ac single location and 3.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

125.0 ac single location and 32.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3500.0 ac single location and 1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

6.000 at 200 pct single location and 41.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Dustproof

Trip Release Ambient Temperature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0