

View Online at <https://aerobasegroup.com/nsn/5925-01-310-1888>

**Body Style:**

Single pole type

**Body Length:**

Between 2.050 inches and 2.070 inches

**Body Width:**

Between 0.970 inches and 0.990 inches

**Body Height:**

Between 1.620 inches and 1.640 inches

**Case Material:**

Plastic

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.310 inches and 0.330 inches

**Pole Quantity:**

1

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

2 clip

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes ac single location and 3.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

125.0 ac single location and 32.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

3500.0 ac single location and 1000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

6.000 at 200 pct single location and 41.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Dustproof

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius single location

**Frequency In Hertz:**

50.0 single location or 60.0 single location

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0