

View Online at <https://aerobasegroup.com/nsn/5925-01-310-9297>

Body Style:

Single pole type

Bushing Length:

0.390 inches

Body Length:

1.130 inches

Body Width:

0.570 inches

Case Material:

Plastic

Mounting Surface To Terminal End Distance:

2.260 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

27

Maximum Continuous Load Current Rating Per Pole:

1.5 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location and 24.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Reset

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 200 pct single location and 40.000 at 200 pct single location and 3.000 at 300 pct single location and 18.000 at 300 pct single location and 2.000 at 400 pct single location and 9.000 at 400 pct single location and 1.000 at 500 pct single location and 6.000 at 500 pct single location and 0.600 at 600 pct single location and 5.000 at 600 pct single location and 0.200 at 1000 pct single location and 2.500 at 1000 pct single location

Trip Release Ambient Temperature Rating:

68.0 degrees fahrenheit single location

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0