NSN 5925-01-311-3079



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-311-3079 **Body Style:** Rectangular dimensional envelope **Overall Length:** 3.060 inches **Overall Height:** 2.000 inches **Overall Width:** 2.960 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity: Mounting Facility Type And Quantity:** 4 terminal Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 50.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:** 2 toggle

Actuator Function: Trip-reset

NSN 5925-01-311-3079

Circuit Breaker - Page 2 of 2



Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
General purpose
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
2 clip and 2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A030a0