## NSN 5925-01-311-3085

Circuit Breaker - Page 1 of 2

Overcurrent all locations



View Online at https://aerobasegroup.com/nsn/5925-01-311-3085

Body Style:
Multipole-single actuator type
Body Length:
6.000 inches
Body Width:
4.125 inches
Body Height:
3.188 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
5.063 inches
Center To Center Distance Between Terminals Parallel To Width:
1.375 inches
Unthreaded Mounting Hole Diameter:
0.164 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.282 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.375 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.312 inches
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
4 unthreaded hole
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Maximum Continuous Load Current Rating Per Pole:
15.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
600.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
18000.0 ac all locations
Circuit Protection Type:

## **NSN 5925-01-311-3085** Circuit Breaker - Page 2 of 2



Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Inclosure Protection Type For Which Designed:
Dustproof
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Unpackaged Unit Weight:
4.750 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A030a0