## NSN 5925-01-311-3087



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-311-3087 **Body Style:** Multipole-single actuator type **Body Length:** 6.000 inches **Body Width:** 4.125 inches **Body Height:** 3.188 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 5.063 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.375 inches **Unthreaded Mounting Hole Diameter:** 0.164 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 4.282 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.312 inches **Pole Quantity:** 3 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic **Maximum Continuous Load Current Rating Per Pole:** 60.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 

18000.0 ac all locations

**Circuit Protection Type:** 

Overcurrent all locations

## **NSN 5925-01-311-3087** Circuit Breaker - Page 2 of 2



Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Inclosure Protection Type For Which Designed:
Dustproof
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
50.0 all locations or 60.0 all locations
Unpackaged Unit Weight:
4.750 pounds
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0