NSN 5925-01-311-3639

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-311-3639

view Offiline at https://defobasegroup.com/hsh/0925-01-011-5005
Body Style:
Rectangular dimensional envelope
Overall Length:
3.060 inches
Overall Height:
2.000 inches
Overall Width:
2.570 inches
Case Material:
Plastic
Fragility Factor:
Moderately rugged
Pole Quantity:
2
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
4 terminal
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Maximum Continuous Load Current Rating Per Pole:
40.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
10000.0 ac all locations
Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:

2 toggle

NSN 5925-01-311-3639 Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At each pole
External Actuator Linkage Arrangement:
One and two linked
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Dustproof
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
2 clip and 2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A030a0