

View Online at <https://aerobasegroup.com/nsn/5925-01-311-3646>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

3.060 inches

**Overall Height:**

2.000 inches

**Overall Width:**

2.570 inches

**Case Material:**

Plastic

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

2

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 terminal

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

22000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One and two linked

**Internal Trip Release Configuration:**

Series trip all locations

**Inclosure Protection Type For Which Designed:**

Dustproof

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

2 tab w/screw and 2 clip

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0