# NSN 5925-01-311-3649

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-311-3649

# Body Style:

Multipole-single actuator type

# **Body Length:**

10.125 inches

# Body Width:

8.250 inches

### **Case Material:**

Plastic

# Center To Center Distance Between Terminals Parallel To Length:

2.750 inches

# Center To Center Distance Between Terminals Parallel To Width:

# 2.750 inches

**Unthreaded Mounting Hole Diameter:** 

#### 0.196 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

# 7.249 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

2.750 inches

# **Fragility Factor:**

Moderately rugged

# **Boss Height:**

0.219 inches

# Mounting Surface To Terminal End Distance:

9.906 inches

# **Pole Quantity:**

3

# Mounting Facility Type And Quantity:

6 unthreaded hole

# Storage Type:

General purpose warehouse

# **Special Handling Feature:**

Magnetic

#### **Features Provided:**

Adjustable trip release

# Maximum Continuous Load Current Rating Per Pole:

250.0 amperes ac all locations and 250.0 amperes dc all locations

# **Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations and 250.0 dc all locations

# Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

35000.0 ac all locations and 10000.0 dc all locations

#### **Circuit Protection Type:**

Overcurrent all locations

# NSN 5925-01-311-3649

Circuit Breaker - Page 2 of 2



Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1250.0/+2500.0 ac all locations and +1250.0/+2500.0 dc all locations
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
General purpose
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0