NSN 5925-01-311-4625

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-311-4625

| Body Style: |
|---|
| Rectangular dimensional envelope |
| Overall Length: |
| 3.060 inches |
| Overall Height: |
| 2.000 inches |
| Overall Width: |
| 2.570 inches |
| Case Material: |
| Plastic |
| Fragility Factor: |
| Moderately rugged |
| Pole Quantity: |
| 2 |
| Arc Quenching Method: |
| Magnetic blowout |
| Mounting Facility Type And Quantity: |
| 4 terminal |
| Storage Type: |
| General purpose warehouse |
| Special Handling Feature: |
| Magnetic |
| Maximum Continuous Load Current Rating Per Pole: |
| 15.0 amperes ac all locations |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 240.0 ac all locations |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 22000.0 ac all locations |
| Circuit Protection Type: |
| Overcurrent all locations |
| Trip Release Method: |
| Magnetic all locations |
| Trip Release Characteristic: |
| Instantaneous all locations |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 125.0 all locations |
| Reset Method: |
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| |

2 toggle

NSN 5925-01-311-4625 Circuit Breaker - Page 2 of 2



| Actuator Function: |
|---|
| Trip-reset |
| Actuator Position Designation: |
| At each pole |
| External Actuator Linkage Arrangement: |
| One and two linked |
| Internal Trip Release Configuration: |
| Series trip all locations |
| Inclosure Protection Type For Which Designed: |
| Dustproof |
| Frequency In Hertz: |
| 50.0 all locations or 60.0 all locations |
| Terminal Type And Quantity: |
| 2 tab w/screw and 2 clip |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |