

View Online at <https://aerobasegroup.com/nsn/5925-01-311-4627>

**Body Style:**

Single pole type

**Body Length:**

2.844 inches

**Body Width:**

2.000 inches

**Body Height:**

2.922 inches

**Case Material:**

Plastic

**Switch Contact Arrangement:**

Single pole, double throw

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.187 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

2 terminal

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

10000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

1 alarm

**Switch Location And Position Designation:**

External at pole one

**Inclosure Protection Type For Which Designed:**

Dustproof

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Switch Terminal Type:**

Tab w/screw

**Switch Current Rating And Type In Amps:**

6.0 ac and 0.25 dc

**Switch Voltage Rating And Type In Volts:**

240.0 ac and 250.0 dc

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

1 clip and 1 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0