

View Online at <https://aerobasegroup.com/nsn/5925-01-311-8328>

**Body Style:**

Multipole-single actuator type

**Body Length:**

Between 5.984 inches and 6.015 inches

**Body Width:**

Between 4.484 inches and 4.516 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 5.109 inches and 5.141 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 1.484 inches and 1.516 inches

**Unthreaded Mounting Hole Diameter:**

0.164 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 4.578 inches and 4.610 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 1.484 inches and 1.516 inches

**Boss Height:**

Between 0.203 inches and 0.235 inches

**Mounting Surface To Terminal End Distance:**

Between 3.984 inches and 4.015 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

15000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Auxiliary Switch Function And Quantity:**

2 alarm

**Switch Location And Position Designation:**

Internal between pole two and three

**Inclosure Protection Type For Which Designed:**

Fungus proof and general purpose

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Switch Terminal Type:**

Wire lead

**Special Features:**

Includes 3 tulip connectors for line side and 3 tulip connectors for load side

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0