NSN 5925-01-313-3894

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-313-3894 **Overall Length:** 210.0 millimeters **Overall Height:** 110.0 millimeters **Overall Width:** 180.0 millimeters **Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 terminal Storage Type: General purpose warehouse **Features Provided:** Adjustable trip release **Maximum Continuous Load Current Rating Per Pole:** 100.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 14000.0 ac all locations **Circuit Protection Type:** Undervoltage all locations **Trip Release Method:** Thermal all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free **Manual Actuator Type And Quantity:**

1 rotary **Actuator Function:** Trip-reset **Actuator Position Designation:** Between pole one and two

NSN 5925-01-313-3894

Circuit Breaker - Page 2 of 2

Fiig: A030a0



Adjustable Trip Setting Current Range Per Pole In Amps:
+600.0/+1200.0 ac all locations
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No