

View Online at <https://aerobasegroup.com/nsn/5925-01-314-4936>

**Body Style:**

Multipole-single actuator type

**Body Length:**

2.000 inches

**Body Width:**

2.170 inches

**Body Height:**

1.925 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

0.625 inches

**Boss Height:**

0.125 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 clip

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

3.000 at 200 pct all locations and 30.000 at 200 pct all locations

**Special Features:**

An illuminated handle

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0