

View Online at <https://aerobasegroup.com/nsn/5925-01-314-5513>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

2.244 inches

**Overall Height:**

0.788 inches

**Overall Width:**

1.807 inches

**Case Material:**

Plastic

**Nonturn Device Location:**

At 12 oclock

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes ac single location and 15.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

275.0 ac single location and 60.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 ac single location and 500.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

60.000 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Humidity resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Frequency In Hertz:**

60.0 single location

**Unpackaged Unit Weight:**

2.300 ounces

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

2 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0