

View Online at <https://aerobasegroup.com/nsn/5925-01-314-5514>

Body Style:

Rectangular dimensional envelope

Overall Length:

2.244 inches

Overall Height:

0.788 inches

Overall Width:

1.807 inches

Case Material:

Plastic

Nonturn Device Location:

At 12 oclock

Fragility Factor:

Moderately rugged

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

1.0 amperes ac single location and 1.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

275.0 ac single location and 60.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac single location and 300.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push button

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

60.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Humidity resistant

Trip Release Ambient Temperature Rating:

20.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Unpackaged Unit Weight:

2.300 ounces

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0