NSN 5925-01-314-8121

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-314-8121

View Online at https://aerobasegroup.com/nsn/5925-01-314-8121
Body Style:
Rectangular dimensional envelope
Overall Length:
210.0 millimeters
Overall Height:
109.000 millimeters
Overall Width:
180.0 millimeters
Case Material:
Plastic
Fragility Factor:
Moderately rugged
Pole Quantity:
3
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
6 terminal
Storage Type:
General purpose warehouse
Features Provided:
Adjustable trip release
Maximum Continuous Load Current Rating Per Pole:
80.0 amperes ac all locations
Operating Voltage Type And Rating Per Pole In Volts:
500.0 ac all locations
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
14000.0 ac all locations
Circuit Protection Type:
Undervoltage all locations
Trip Release Method:
Thermal all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:

1 rotary

NSN 5925-01-314-8121

Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Adjustable Trip Setting Current Range Per Pole In Amps:
+260.0/+500.0 ac all locations
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
.
Demilitarization:
No
Fiig:
A030a0