

View Online at <https://aerobasegroup.com/nsn/5925-01-314-8125>

Body Style:

Rectangular dimensional envelope

Overall Length:

210.0 millimeters

Overall Height:

109.000 millimeters

Overall Width:

180.0 millimeters

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

6 terminal

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac all locations

Circuit Protection Type:

Undervoltage all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 rotary

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Adjustable Trip Setting Current Range Per Pole In Amps:

+160.0/+320.0 ac all locations

Internal Trip Release Configuration:

Series trip all locations

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0