

View Online at <https://aerobasegroup.com/nsn/5925-01-314-8126>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

17.310 inches

**Overall Height:**

5.190 inches

**Overall Width:**

8.250 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.250 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

400.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

150000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Auxiliary Switch Function And Quantity:**

1 alarm

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+2000.0/+3200.0 ac all locations

**Internal Trip Release Configuration:**

Series trip all locations

**Switch Location And Position Designation:**

Internal at pole one

**Inclosure Protection Type For Which Designed:**

Dustproof and fungus proof

**Switch Current Rating And Type In Amps:**

15.0 ac and 0.5 dc

**Switch Voltage Rating And Type In Volts:**

250.0 ac and 125.0 dc

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0