

View Online at <https://aerobasegroup.com/nsn/5925-01-315-1896>

Body Style:

Multipole-single actuator type

Body Length:

Between 22.115 inches and 22.260 inches

Body Width:

Between 12.053 inches and 12.073 inches

Body Height:

Between 9.928 inches and 9.948 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 14.428 inches and 14.448 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 4.021 inches and 4.041 inches

Unthreaded Mounting Hole Diameter:

Between 0.709 inches and 0.729 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 19.866 inches and 19.886 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 4.021 inches and 4.041 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.740 inches and 0.760 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

1600.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

100000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Adjustable Trip Setting Current Range Per Pole In Amps:

+3200.0/+12800.0 ac all locations

Internal Trip Release Configuration:

Series trip all locations

Inclosure Protection Type For Which Designed:

General purpose

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0