

View Online at <https://aerobasegroup.com/nsn/5925-01-315-1896>

**Body Style:**

Multipole-single actuator type

**Body Length:**

Between 22.115 inches and 22.260 inches

**Body Width:**

Between 12.053 inches and 12.073 inches

**Body Height:**

Between 9.928 inches and 9.948 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 14.428 inches and 14.448 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 4.021 inches and 4.041 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.709 inches and 0.729 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 19.866 inches and 19.886 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 4.021 inches and 4.041 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.740 inches and 0.760 inches

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

1600.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

100000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+3200.0/+12800.0 ac all locations

**Internal Trip Release Configuration:**

Series trip all locations

**Inclosure Protection Type For Which Designed:**

General purpose

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0