

View Online at <https://aerobasegroup.com/nsn/5925-01-315-3202>

Body Length:

6.000 inches

Body Width:

1.375 inches

Body Height:

3.375 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.164 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.125 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

60.0 amperes ac single location and 60.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

277.0 ac single location and 125.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac single location and 10000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Inclosure Protection Type For Which Designed:

Dustproof

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0