

View Online at <https://aerobasegroup.com/nsn/5925-01-315-3203>

Body Style:

Multipole-multiple actuator type

Body Length:

Between 2.468 inches and 2.532 inches

Body Width:

Between 1.480 inches and 1.520 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.906 inches and 1.970 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.718 inches and 0.782 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 2.030 inches and 2.094 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.718 inches and 0.782 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.108 inches and 0.172 inches

Mounting Surface To Terminal End Distance:

Between 2.579 inches and 2.643 inches

Pole Quantity:

2

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

75.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

65.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

2 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One and two linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.500 at 200 pct all locations and 7.500 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Dustproof and fungus proof

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0