

View Online at <https://aerobasegroup.com/nsn/5925-01-315-3806>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

9.120 inches

**Overall Height:**

5.380 inches

**Overall Width:**

Between 8.240 inches and 8.250 inches

**Case Material:**

Plastic

**Unthreaded Mounting Hole Diameter:**

0.310 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Storage Type:**

General purpose warehouse

**Features Provided:**

Adjustable trip release

**Maximum Continuous Load Current Rating Per Pole:**

400.0 amperes ac all locations and 400.0 amperes dc all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations and 250.0 dc all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

22000.0 ac all locations and 10000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

4 alarm

**Adjustable Trip Setting Current Range Per Pole In Amps:**

+1200.0/+4000.0 ac all locations and +1200.0/+4000.0 dc all locations

**Switch Location And Position Designation:**

External at pole three

**Inclosure Protection Type For Which Designed:**

General purpose

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Switch Terminal Type:**

Wire lead

**Switch Current Rating And Type In Amps:**

6.0 ac and 0.250 dc

**Switch Voltage Rating And Type In Volts:**

240.0 ac and 250.0 dc

**Special Features:**

48 vdc shunt trip with wire leads installed on right side of circuit breaker; 120 vac motor operator mounted on front of circuit breaker, 5.750 inch lg, 3.230 inch w, 10.120 inch h

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0