

View Online at <https://aerobasegroup.com/nsn/5925-01-315-6349>

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.219 inches and 0.281 inches

Body Length:

1.840 inches

Body Width:

0.781 inches

Body Height:

1.381 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 0.593 inches and 0.655 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.469 inches and 0.531 inches

End Application:

Periscope

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

200.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct all locations and 20.000 at 200 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0