

View Online at <https://aerobasegroup.com/nsn/5925-01-317-9966>

Body Style:

Multipole-single actuator type

Bushing Length:

0.495 inches

Body Length:

2.000 inches

Body Width:

1.500 inches

Center To Center Distance Between Terminals Parallel To Length:

1.530 inches

Center To Center Distance Between Terminals Parallel To Width:

0.750 inches

Mounting Surface To Terminal End Distance:

2.200 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

0.5 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Auxiliary Switch Function And Quantity:

1 control

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal all locations

Thread Size:

0.500 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

0.500 at 150 pct all locations and 8.000 at 150 pct all locations and 0.150 at 200 pct all locations and 1.900 at 200 pct all locations and 0.020 at 400 pct all locations and 0.400 at 400 pct all locations and 0.006 at 600 pct all locations and 0.250 at 600 pct all locations and 0.004 at 800 pct all locations and 0.100 at 800 pct all locations and 0.004 at 1000 pct all locations and 0.050 at 1000 pct all locations

Inclosure Protection Type For Which Designed:

Moisture resistant and corrosion resistant and shock resistant and vibration resistant

Switch Terminal Type:

Quick disconnect, male

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Un

Terminal Type And Quantity:

10 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0