## NSN 5925-01-318-3296

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-318-3296

#### **Body Style:**

Multipole-single actuator type

#### **Body Length:**

10.000 inches

### Body Width:

4.125 inches

#### **Body Height:**

4.062 inches

#### **Case Material:**

Plastic

#### Center To Center Distance Between Terminals Parallel To Length:

#### 9.000 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.375 inches

**Unthreaded Mounting Hole Diameter:** 

#### 0.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

7.250 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.375 inches

#### **Fragility Factor:**

Moderately rugged

#### **Boss Height:**

0.250 inches

#### Pole Quantity:

3

#### Arc Quenching Method:

Magnetic blowout

#### Mounting Facility Type And Quantity:

4 unthreaded hole

#### Storage Type:

General purpose warehouse

#### **Special Handling Feature:**

Magnetic

#### Features Provided:

Adjustable trip release

#### Maximum Continuous Load Current Rating Per Pole:

100.0 amperes ac all locations and 100.0 amperes dc all locations

#### **Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations and 250.0 dc all locations

#### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations and 10000.0 dc all locations

# NSN 5925-01-318-3296

Circuit Breaker - Page 2 of 2



Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+160.0/+240.0 ac all locations and +160.0/+240.0 dc all locations
Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Dustproof
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0