NSN 5925-01-320-2497

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-320-2497

Body Style:
Single pole type
Body Length:
2.000 inches
Body Width:
0.750 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.530 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
1.660 inches
Fragility Factor:
Moderately rugged
Boss Height:
0.130 inches
Mounting Surface To Terminal End Distance:
1.890 inches
Pole Quantity:
1
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
2 threaded hole
Storage Type:
General purpose warehouse
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
3.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
277.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
5000.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic-hydraulic single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

NSN 5925-01-320-2497 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.150 at 200 pct single location and 1.500 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and humidity resistant and moisture resistant and shock resistant and vibration resistant
Frequency In Hertz:
50.0 single location or 60.0 single location
Unpackaged Unit Weight:
3.000 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filig:
A030a0