

View Online at <https://aerobasegroup.com/nsn/5925-01-321-1389>

**Unthreaded Mounting Hole Diameter:**

0.172 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 unthreaded hole

**Features Provided:**

Trip indicator

**Maximum Continuous Load Current Rating Per Pole:**

60.0 amperes ac single location and 60.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

115.0 ac single location and 28.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

3600.0 ac single location and 3600.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal single location

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

115.0 ac single location and 28.0 dc single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Electric

**Main Contact Tripping Mechanism Type:**

Trip free

**Internal Trip Release Configuration:**

Series trip w/auxiliary load terminal and remote trip feature single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

13.000 at 200 pct single location and 60.000 at 200 pct single location and 2.600 at 400 pct single location and 13.000 at 400 pct single location and 0.260 at 1000 pct single location and 1.800 at 1000 pct single location

**Inclosure Protection Type For Which Designed:**

Dustproof and sand resistant and humidity resistant and corrosion resistant and explosion resistant and moisture resistant and shock resistant and vibration resistant

**Trip Release Ambient Temperature Rating:**

25.0 degrees celsius single location

**Frequency In Hertz:**

400.0 single location

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0