

View Online at <https://aerobasegroup.com/nsn/5925-01-321-1389>

Unthreaded Mounting Hole Diameter:

0.172 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Features Provided:

Trip indicator

Maximum Continuous Load Current Rating Per Pole:

60.0 amperes ac single location and 60.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3600.0 ac single location and 3600.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Auxiliary Trip Coil Voltage Type And Rating In Volts:

115.0 ac single location and 28.0 dc single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Electric

Main Contact Tripping Mechanism Type:

Trip free

Internal Trip Release Configuration:

Series trip w/auxiliary load terminal and remote trip feature single location

Trip Delay Time In Seconds Per Rated Continuous Current:

13.000 at 200 pct single location and 60.000 at 200 pct single location and 2.600 at 400 pct single location and 13.000 at 400 pct single location and 0.260 at 1000 pct single location and 1.800 at 1000 pct single location

Inclosure Protection Type For Which Designed:

Dustproof and sand resistant and humidity resistant and corrosion resistant and explosion resistant and moisture resistant and shock resistant and vibration resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0