

View Online at <https://aerobasegroup.com/nsn/5925-01-321-8895>

Body Style:

Multipole-single actuator type

Body Length:

6.440 inches

Body Width:

4.500 inches

Body Height:

3.160 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

5.570 inches

Center To Center Distance Between Terminals Parallel To Width:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

4.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Fragility Factor:

Moderately rugged

Boss Height:

0.190 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

3 clip and 3 terminal

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

110.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

3 compression and 3 bus bar

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0