# NSN 5925-01-321-8895

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-321-8895

## **Body Style:**

Multipole-single actuator type

### **Body Length:**

6.440 inches

## Body Width:

4.500 inches

### **Body Height:**

3.160 inches

#### **Case Material:**

Plastic

## Center To Center Distance Between Terminals Parallel To Length:

#### 5.570 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 4.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

## **Fragility Factor:**

Moderately rugged

### **Boss Height:**

0.190 inches

#### Pole Quantity:

3

## Mounting Facility Type And Quantity:

3 clip and 3 terminal

## Storage Type:

General purpose warehouse

## Maximum Continuous Load Current Rating Per Pole:

110.0 amperes ac all locations

## **Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22000.0 ac all locations

#### **Circuit Protection Type:**

Overcurrent all locations

#### **Trip Release Method:**

Thermal-magnetic all locations

#### **Trip Release Characteristic:**

Instantaneous all locations

#### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

# NSN 5925-01-321-8895

Circuit Breaker - Page 2 of 2



#### **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

**Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

At pole two

Inclosure Protection Type For Which Designed:

General purpose

**Trip Release Ambient Tempurature Rating:** 

40.0 degrees celsius all locations

## Frequency In Hertz:

60.0 all locations

## **Terminal Type And Quantity:**

3 compression and 3 bus bar

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0