

View Online at <https://aerobasegroup.com/nsn/5925-01-322-2046>

**Thread Pitch Diameters:**

+0.1177/+0.1214 inches

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

2.500 inches

**Body Width:**

1.515 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 1.920 inches and 1.960 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.745 inches and 0.755 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 2.050 inches and 2.070 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 0.745 inches and 0.755 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.135 inches and 0.165 inches

**Mounting Surface To Terminal End Distance:**

Between 2.444 inches and 2.506 inches

**Pole Quantity:**

2

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

4 threaded hole

**Storage Type:**

General purpose warehouse

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

35.0 amperes dc first location

**Operating Voltage Type And Rating Per Pole In Volts:**

65.0 dc first location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac second location

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Auxiliary Trip Coil Voltage Type And Rating In Volts:**

25.0 dc all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

115.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One and two linked

**Internal Trip Release Configuration:**

Series/relay trip all locations

**Thread Size:**

0.134 inches

**Trip Release Duty Cycle:**

Continuous all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.700 at 200 pct first location and 10.000 at 200 pct first location

**Inclosure Protection Type For Which Designed:**

Vibration resistant and shock resistant and moisture resistant and salt spray proof

**Frequency In Hertz:**

60.0 second location

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

8 threaded stud

**Specification Data:**

95266-414-00005-08 manufacturers source control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0