NSN 5925-01-323-0238

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-323-0238

Body Style: Single pole type **Body Length:** Between 1.550 inches and 1.570 inches **Body Width:** Between 0.760 inches and 0.780 inches **Body Height:** Between 1.810 inches and 1.870 inches Case Material: **Plastic Switch Contact Arrangement:** Single pole, double throw **Fragility Factor:** Moderately rugged **Boss Height:** Between 0.083 inches and 0.103 inches **Pole Quantity:** 1 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 2 clip Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 2.0 amperes ac single location and 2.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location and 65.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac single location and 1000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type:**

Trip free

NSN 5925-01-323-0238

Circuit Breaker - Page 2 of 2



| Manual Actuator Type And Quantity: |
|--|
| 1 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At pole one |
| Auxiliary Switch Function And Quantity: |
| 1 alarm |
| Internal Trip Release Configuration: |
| Series trip single location |
| Switch Location And Position Designation: |
| External at pole one |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 1.000 at 200 pct single location and 15.000 at 200 pct single location |
| Inclosure Protection Type For Which Designed: |
| Dustproof and fungus proof |
| Switch Terminal Type: |
| Tab, solder lug |
| Switch Current Rating And Type In Amps: |
| 3.0 ac and 1.5 dc |
| Switch Voltage Rating And Type In Volts: |
| 120.0 ac and 32.0 dc |
| Frequency In Hertz: |
| 50.0 single location or 60.0 single location |
| Terminal Type And Quantity: |
| 2 quick disconnect, male |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A030a0 |
| |
| |