

View Online at <https://aerobasegroup.com/nsn/5925-01-323-1612>

**Body Style:**

Multipole-single actuator type

**Body Length:**

280.5 millimeters

**Body Width:**

252.0 millimeters

**Body Height:**

110.0 millimeters

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

252.0 millimeters

**Center To Center Distance Between Terminals Parallel To Width:**

95.0 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

210.0 millimeters

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

66.0 millimeters

**Fragility Factor:**

Moderately rugged

**Boss Height:**

16.0 millimeters

**Pole Quantity:**

3

**Arc Quenching Method:**

Magnetic blowout

**Mounting Facility Type And Quantity:**

6 terminal

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

2.1 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

600.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

14000.0 ac all locations

**Circuit Protection Type:**

Undervoltage all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 rotary

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Inclosure Protection Type For Which Designed:**

Dustproof

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

6 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0