

View Online at <https://aerobasegroup.com/nsn/5925-01-324-3468>

Body Style:

Multipole-single actuator type

Body Length:

10.125 inches

Body Width:

5.490 inches

Body Height:

4.062 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

8.975 inches

Center To Center Distance Between Terminals Parallel To Width:

1.719 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

8.350 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.719 inches

End Application:

Ships service generator and power supply onboard 400 ft wagb c.G. Vessels

Boss Height:

0.188 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

225.0 amperes ac all locations and 225.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

25000.0 ac all locations and 10000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal-magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

115.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Trip Delay Time In Seconds Per Rated Continuous Current:

150.000 at 150 pct all locations

Trip Release Ambient Temperature Rating:

40.0 degrees celsius all locations

Special Features:

120.0 volt under voltage release included, 60.0 in. Wire leads included with item

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0