

View Online at <https://aerobasegroup.com/nsn/5925-01-325-4361>

**Body Style:**

Multipole-single actuator type

**Body Length:**

2.000 inches

**Body Width:**

2.170 inches

**Body Height:**

1.770 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.595 inches and 0.655 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

Between 0.005 inches and 0.155 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

2 clip

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Maximum Continuous Load Current Rating Per Pole:**

500.0 milliamperes dc third location

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc third location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 dc third location

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 rotary

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.500 at 200 pct third location and 9.000 at 200 pct third location

**Inclosure Protection Type For Which Designed:**

Shockproof and vibrationproof

**Frequency In Hertz:**

50.0 second location or 60.0 second location

**Unpackaged Unit Weight:**

3.900 ounces

**Terminal Type And Quantity:**

6 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0