

View Online at <https://aerobasegroup.com/nsn/5925-01-325-4404>

Body Style:

Single pole type

Bushing Length:

0.260 inches

Body Length:

1.220 inches

Body Width:

0.710 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.930 inches

Nonturn Device Location:

At 12 oclock

Nonturn Device Length:

0.060 inches

Nonturn Device Width:

0.110 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.730 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location and 10.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

3500.0 ac single location and 6000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

0.480 at 200 pct single location and 10.500 at 200 pct single location

Inclosure Protection Type For Which Designed:

Dustproof and fungus proof and vibrationproof and corrosion resistant and humidity proof

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0