## NSN 5925-01-325-5238

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-325-5238

**Body Style:** Rectangular dimensional envelope **Overall Length:** 10.250 inches **Overall Height:** 18.312 inches **Overall Width:** 13.688 inches **Case Material:** Metal **End Application:** Circuit breakers **Pole Quantity: Mounting Facility Type And Quantity:** 4 threaded stud **Maximum Continuous Load Current Rating Per Pole:** 900.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 500.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 60000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Solid state all locations **Trip Release Characteristic:** Instantaneous all locations and time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 225.0 all locations **Ultimate Trip Time Per Pole In Seconds:** 30.000 all locations **Reset Method:** Manual **Manual Actuator Type And Quantity:** 3 toggle **Actuator Function:** Reset **Trip Delay Time In Seconds Per Rated Continuous Current:** 

10.000 at 225 pct all locations and 30.000 at 225 pct all locations

**Switch Voltage Rating And Type In Volts:** 

120.0 ac

## NSN 5925-01-325-5238

Circuit Breaker - Page 2 of 2



	Freq	uency	In I	Hertz:
--	------	-------	------	--------

60.0 all locations

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A030a0