

View Online at <https://aerobasegroup.com/nsn/5925-01-325-5238>

Body Style:

Rectangular dimensional envelope

Overall Length:

10.250 inches

Overall Height:

18.312 inches

Overall Width:

13.688 inches

Case Material:

Metal

End Application:

Circuit breakers

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 threaded stud

Maximum Continuous Load Current Rating Per Pole:

900.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

500.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

60000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Solid state all locations

Trip Release Characteristic:

Instantaneous all locations and time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

225.0 all locations

Ultimate Trip Time Per Pole In Seconds:

30.000 all locations

Reset Method:

Manual

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Reset

Trip Delay Time In Seconds Per Rated Continuous Current:

10.000 at 225 pct all locations and 30.000 at 225 pct all locations

Switch Voltage Rating And Type In Volts:

120.0 ac

Frequency In Hertz:

60.0 all locations

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0