NSN 5925-01-327-0943

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-327-0943

Body Style:

Multipole-single actuator type

Body Length:

14.000 inches

Body Width:

9.000 inches

Body Height:

4.530 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

10.690 inches

Center To Center Distance Between Terminals Parallel To Width:

3.000 inches

Unthreaded Mounting Hole Diameter:

0.196 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

10.690 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Fragility Factor:

Moderately rugged

Boss Height:

1.970 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

 $350.0 \ \text{amperes} \ \text{ac} \ \text{all} \ \text{locations} \ \text{and} \ 350.0 \ \text{amperes} \ \text{dc} \ \text{all} \ \text{locations}$

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations and 250.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

22000.0 ac all locations and 14000.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

NSN 5925-01-327-0943

Circuit Breaker - Page 2 of 2



Trip Release Method:
Thermal-magnetic all locations
Trip Release Characteristic:
Instantaneous all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Adjustable Trip Setting Current Range Per Pole In Amps:
+1750.0/+3500.0 ac all locations and +1750.0/+3500.0 dc all locations
Inclosure Protection Type For Which Designed:
Dustproof
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
4000-0

A030a0