NSN 5925-01-330-0488

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-330-0488

Body Style:

Rectangular dimensional envelope

Overall Length:

38.406 inches

Overall Height:

5.062 inches

Overall Width:

11.468 inches

Case Material:

Plastic

Fragility Factor:

Moderately rugged

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

4 unthreaded hole

Storage Type:

General purpose warehouse

Features Provided:

Adjustable trip release

Maximum Continuous Load Current Rating Per Pole:

250.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

18000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

NSN 5925-01-330-0488

Circuit Breaker - Page 2 of 2



Actuator Function: Trip-reset **Actuator Position Designation:** At pole two Adjustable Trip Setting Current Range Per Pole In Amps: +1100.0/+2500.0 ac all locations Internal Trip Release Configuration: Series trip all locations Inclosure Protection Type For Which Designed: Dustproof and fungus proof **Trip Release Ambient Tempurature Rating:** 50.0 degrees celsius all locations **Frequency In Hertz:** 60.0 all locations **Terminal Type And Quantity:** 6 compression Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A030a0