NSN 5925-01-330-2355



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-330-2355 **Overall Length:** 17.500 inches **Overall Height:** 5.062 inches **Overall Width: 7.500 inches Case Material: Plastic Fragility Factor:** Moderately rugged **Pole Quantity:** 3 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 125.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 600.0 ac all locations **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 18000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal all locations **Trip Release Characteristic:** Instantaneous all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

NSN 5925-01-330-2355

Circuit Breaker - Page 2 of 2



Internal Trip Release Configuration:
Series trip all locations
Inclosure Protection Type For Which Designed:
Dustproof and fungus proof
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Terminal Type And Quantity:
6 compression
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A030a0